



# HANDWRITTEN NOTES

---

Download FREE Notes for Computer Science and related resources only at

[Kwiknotes.in](https://kwiknotes.in)

Don't forget to check out our social media handles, do share with your friends.



## TRADITIONAL FILE SYSTEM

A manual file system was used to maintain the records and the files. Data was stored and processed using a traditional file system which makes it easy to find information.

- In a file processing system (FPS), each file is dependent on each other and they can only be integrated by writing individual program for each application.
- The data and app program that uses data are arranged and any changes to data sometimes require modification of application program.
- Sometimes it is not possible to identify all the programs using data; all functional areas in the organisation itself creates and processes its own files.


## Features of traditional file system

- It stores data in group of files.
- Files are dependent on each other.
- It is difficult to maintain traditional FS.
- TFS is also called Flat FS.

## FUNCTIONS

- Stores and arrange comp files
- Stores files in database, manipulated and retrieved by computer OS.
- It performs services for end users.
- Inserting, deleting, updating and adding new files to existing DB.

- Each program defines and manages its own data



### DISADVANTAGE

- Data Redundancy (duplicate data)  
Each app has its own data, same data may have to be recorded or stored many times
- Data inconsistency  
Due to the same data items that appear more than once and don't get updated simultaneously in each and every file
- Data Dependency  
Program in app in FPS are data dependent because of incompatibility with various file formats.
- Limited data sharing
- Security
- Retrieval is not easy.
- Time Consuming.
- Requires labour
- Inefficient to maintain the record of a big org having large amt of data items.

collection of program used for managing data

Undo - old value  
Redo - new value

classmate

Date \_\_\_\_\_  
Page \_\_\_\_\_

Database — It is an organised collection of set of data used to serve some special purpose or  
A database is a collection of data with some inherent meaning, representing some aspect of real world and designed, built and populated with data for a specific purpose.

### DBMS

It is a collection of app programs that enables a user to create and maintain a database. OR It is a general purpose software system that provides the user with the processes of defining, constructing and manipulating the database for various applications.

### Advantages

- 1) Data is stored in a structured way
- 2) Redundancy is controlled.
- 3) It consumes less space.
- 4) Unauthorized access is denied.
- 5) It provides multiple user interface.
- 6) Providing data backup and recovery (Undo & Redo)
- 7) Data Security and integrity
- 8) Concurrency Control.
- 9) Data independence


up Levels of Data Abstraction / Three schema arch.

Single data = datum

classmate

Date \_\_\_\_\_

Page \_\_\_\_\_



→ Physical Level

1) Lowest level of Abstraction which describes how data are stored

2) Physical level also called internal level

→ Logical Level

1) This is the next higher level of abstraction describes what data are stored and what relationship holds b/w data.

2) The logical level is also as conceptual level.

→ External Level

1) This is the highest level of abstractions describes only a part of entire database.

2) External level is also called as view level.

## Advantage of DBMS.

### 1) Data Independence

The ability to modify schema definition at one level without affecting a schema definition in next higher level is called data independence.

2 types of data independence:

- Physical data independence - ability to change schema in physical level without affecting the change in conceptual and external level.
- Logical data independence - the ability to change schema in logical level without affecting the change in external level.

### 2) Schemas and Instance

The overall design of database is called schema and schema include schema objects like table, Primary Key, foreign Key, columns, datatypes, etc.

#### Instance

The data stored in database at a particular moment of time is called an instance of database.

## Types of database users:

- Application Programmers: they develop application program and these programs can manipulate the database in all possible ways
- End users: the end users access the database from a terminal using a query language provided by the database system or through the application programs developed by app programmers.

### Database Administrator (DBA)


Is the person who is responsible for design, construction and maintenance and the refrain the illegal access into the database.

Naive users: which hardly knows anything about database

### → Database Architecture:

DBMS depends upon its architecture which is basically a client server architecture used to deal with the large number of personal computers, web servers, database servers and other components that are connected with the network.


- The Client - server architecture consist of many personal computers and workstations which are connected via network.
- DBMS architecture depends upon how users are connected to database to get their request done.



1-tier : in this architecture, database is directly available to user. It means user can directly sit on DBMS and use it. Any changes done here will directly be done on database itself.

It does not provide handy tools for end users. 1-tier architecture is used for development of local applications, where programmers can directly communicate with the database for quick response.

## 2 tier architecture



- 2 tier architecture is as same as Client server architecture
- In 2 tier architecture applications on the client end can directly communicate with database at the server side. For this interaction, API's are used like ODBC (Open database connectivity), JDBC (Java Database connectivity)
- The user interface and app programs are done on Client side
- The server side is responsible to provide functionality like query processing and transaction management
- To communicate with the DBMS, Client side application establishes a connection with server side.


used in web applications.

classmate

Date \_\_\_\_\_

Page \_\_\_\_\_

~~up~~  
3 tier



- The 3 tier architecture contains a layer between Client and Server. In this Architecture, client cannot directly communicate with server. The application on client end interacts with an application server which further communicates with database system. End user has no idea about the existence of database beyond application server. The database also has no idea about any other user beyond the application.
- It is used in large web applications.

30 Oct

DBMSFile Processing SystemApplications

- |   |  |                              |
|---|--|------------------------------|
| 1) Data Redundancy (duplication) problem is not found in DBMS.        | 1) This problem exist here.                                      | 1) Banking, account, banking |
| 2) Data inconsistency problem doesn't exist                           | 2) This problem exist here.                                      | 2) University, course        |
| 3) Problem of data isolation is not found here.                       | 3) Data are scattered in various files and in different formats. | 3) Railway of different      |
| 4) Accessing the database is easier                                   | 4) Accessing database in files is comparatively difficult.       | 4) Airlines                  |
| 5) Atomicity and integrity problem are not found here.                | 5) Both problem are found here.                                  | 5) Telecom calls             |
| 6) Data is secured in DBMS  | 6) Data not secured in FPS                                       | 6) Sales information         |
| 7) Concurrent access and crash recovery procedures are found in DBMS. | 7) No concurrent access and crash recovery proc. in FPS.         | * COM                        |

Data Integrity


Refers to ensuring that the data in database is accurate. Since in DBMS data is centralized and is used by no. of users at a time same time. So it is essential to enforce integrity constraints.

DBMS  
User  
Interf

## Applications of DBMS

- 1) Banking: For maintaining customer information, accounts information, notes inf and banking transaction.
- 2) Universities: For maintaining student record, course registration and results.
- 3) Railway Reservation: for checking availability of different trains, tickets.
- 4) Airlines: for reservation & schedule info.
- 5) Telecommunication: for keeping records of calls, generating monthly bills, etc.
- 6) Sales: for customer, product and purchase information.

## \* COMPONENTS OF DBMS




- The user request for a specific information with the help of user interface i.e application programs
- This request is processed by Data Manager and after processing, data manager request for specific records to file manager
- The file manager then request for the specific block to disk manager
- The disk manager retrieves the record from physical database and then sends the data to disk manager and disk manager sends the data to file manager and file manager sends back the data to data manager and the response of query is again sent to the requested user
- The transaction manager supervises (control) the data transaction i.e carried out between data manager and disk manager
- The recovery manager keeps a check on transacted data so that in case of system failure the data can be protected

6 Oct

DDA

Digital Differential Analogy



Terms related to database

i) Extension

It is the number of tuples present in table at any instance. It is time dependent

ii) Intension

It is a constant value that gives the name, structure of table and constraint lays laid on it

iii) View Table

A table that doesn't really exist in its own derivation and it can be derived from one or base table. Growth and restructuring of base table is not reflected in view table

iv) Data Model. 4p

A data Model is a collection of conceptual tools for describing data, data relationships, data Semantics (sense of data) and constraints.

exp

Data Modelling is a way of organising a collection of information


A Database model is a collection of 2 parts

- A mathematical notation for describing data and relationships
- A set of operations used to manipulate that data

A database model consists of rules & standards that define how data is organised in a database.

There are 4 basic types of <sup>data</sup> models in a database

- Hierarchical model




- It is the oldest form of database
- This data model organises data in a ~~tree~~ tree structure i.e. each child node can have only one parent node. In this model, a database record is a tree that consist of one or more groupings of fields called segments which make up the individual nodes of the tree

The hierarchical model uses parent-child relationship i.e. one-to-many relationship.

The main advantage is that data access is quite predictable in structure and therefore both retrieval and update can be highly optimized in a database.

Disadvantage is one-to-many relationship i.e. it restricts a child node to have only one parent.

### ii) Network MODEL



The network model expands on hierarchical model by providing multiple paths among segments that is more than one parent-child relationship exist.

This model allows 1:1, 1:M, M:1, M:M relationships

The basic data modelling constructs in the network model is Set Construct.

Table → Relation  
Row → Tuple  
Column → attribute

A set consists of set name, records and its types.

A network database stores information in datasets which is similar to files and tables

### iii) Relational Model

Name	id	Add

A relational DB represents data in a database as a 2 dimension table called relation that are logically equivalent to files

Each row of relational table is called a tuple, representing the data entity with columns of table representing attributes.

There are 3 basic operations used to develop sets of data

- i) Selection (whole row)
- ii) Projection (particular field)
- iii) Joins (merge table)

Together with these 3 operations, relational database is called Relational Algebra

It provides flexibility that allows us to change the structure of database.

## ii) OBJECT ORIENTED DATABASE MODEL

- An object oriented database stores & maintain objects
- An object is an item that can contain both data and procedure that manipulates the data.
- As compared to relational database, object oriented DB model can store more types of data and access much faster.
- It uses a query lang called object query lang (OQL) to manipulate and retrieve data.

High level data model, define data elements & relationship

## Entity Relationship Diagram

describe structure of Database

An er model is a high level data model.

It is based on the perception of real world that consist of collection of basic objects called entities and of relationships among these entities.

ER model represent the overall logical structure of a database.


These Schema Architecture

• logical  
• physical  
• external

## \* Entity

- An entity is an Object that has its existence in real world.
- It includes all those things about which data is collected. An entity maybe a tangible object (we can change these things) such as student, place.

It may also be a non tangible objects such as job title, event or a customer account.

- For examples: customer buys goods
- Diagrammatically, entities are represented in rectangles 


Customer

Goods

## \* Attributes

Attributes are units that describe the characteristics or properties of entities. In a DB, entities are represented by table and attributes by column name.

Attributes are drawn in elliptical shape.



The Domain of an attribute is the collection of all the possible values an attribute can have.

## Field / Column

A column represents one related part of a table and is the smallest logical structure of storage in a database. It holds one piece of information about data.

## Record / Row

A record is a collection of multiple related fields that can be treated as a unit. Each row is a record.


## Table


A table is a named collection of logically related multiple records.

## Types of Attributes

Simple attributes are those attributes which cannot be divided into subparts.

Composing attributes are those attributes which can be divided into subparts.





### Single value Attribute

Attribute which has a single value for a particular entity is called single value attribute.

Ex - account number.

### Multivalued Attribute


Attributes which have more than 1 value for a specific entity is called Multivalued attributes.

Multi valued attributes are represented by double oval.

Phone no, Landline




Derived Attributes are represented by dotted oval. The value for this type of attribute can be derived from the value of other related attribute.




Many to one

When more than one instance of an entity is associated with a single instance of another entity.

Many to many


When more than one instance of entity is associated with more than one instance of another entity.



Types of entities:

Strong Entity

An entity that possess sufficient attributes to form a primary key is called a strong entity.




Underlined attributes are primary key attributes

Weak Entity


An entity set that does not possess sufficient attributes to form a primary key is called a weak entity set.

Weak entity is represented by double rectangle




ER Diagram


Entities	Attributes	Relationships
+ Strong	+ Simple	+ One-one
+ Weak	+ Composite	+ One-many
	+ Single-valued	+ Many-one
	+ Multi-valued	+ Many-many
	+ Derived	




# Notations of ER Diagram




Attribute




Primary Key




Composite Attribute



Multivalued Attribute




Derived Attribute



Entity



Strong Entity



Weak Entity



Relationship



links




one to one




one to many




many to many




Q Draw an ER Diagram showing all types of attributes.



Q Draw an ER Diagram for Hospital management system.



Q Draw an ER diagram for college.



Q Draw an ER Diagram for Employee management system.




Table for Multivalued.


Table

Employee
name
id
Projectclass
Salary

Cabin
IT
Sales
acc



## Extended ER Diagram

- 1) Specialization (Top down)
- 2) Generalization (Bottom up)
- 3) Aggregation



1)

- Specialization is top down approach
- In Specialization, one higher level entity can be broken down into two or more lower level entities.
- Specialization is used to identify the subset of an entity set that shares ~~and~~ some different characteristics
- Normally, a superclass is defined first and its related attributes are defined, its subclasses are defined next and their related attributes and at last relationship is added.


The label  is a , ISA stand for is a.

Specialization is depicted by triangle component labelled ISA.

## 2) Generalization

- It is inverse of specialization
- It is like a bottom up approach
- In generalization, two or more lower level entities are combined to form one higher level entity if they have some attributes in common.
- Entities are combined to form a more generalized entity i.e. subclasses are combined to form a superclass.

## 3) Aggregation



process in which entities are combined to form a single meaningful entity. Specific entities are combined bcoz they don't make sense individually. To establish single entity, agg creates a relationship


In aggregation, the relationship of 2 entities

In aggregation, relationships with its corresponding entities is aggregated to a higher level entity.

for ex-


Center entity offers the course entity that acts as a single entity in the relationship which is in a relationship with another entity

### Conversion of ER Diagram



## How to convert an ER diagram to table

- Entity become a table name
- All single value attributes becomes a column for that table
- Primary key attributes are listed in column name
- The multivalued attribute is represented by a separate table
- Composite attribute are listed column name
- Derived attributes are not considered in table



## Relational Model concepts.

A table is a logical construction in relational database management system (RDBMS)

- It is a 2D structure having rows and column
- Rows of a table represent the related records
- And column represents attributes i.e row column intersection gives a single value data called field.
- In RDBMS, rows are called tuples, values within a single column are homogeneous i.e all tuples are having same data format for a single column.
- All attributes have a specific range of values called attribute domain.
- Each tuple in a relation is unique
- The column of a table or relation are assigned a distinct name
- The ordering of the tuples in relation is immaterial.
- Likewise sequence of columns within a relation is of no importance

In RDBMS each table have a primary key  
Row / Record . It contains the specific information  
of each entry in the table.

It is a horizontal entity in the table.

- All tuples have same format.

Column / Attribute : . It is a vertical entity  
in the table .

- Contains all information associated with a  
specific field in a table .

Degree of a table .

The total no. of attributes or columns  
name in a table is the degree of  
entire table .

4. Cardinality of a table - the total no. of  
tuples at any one time in a relation (table)  
is the cardinality of entire relation

⊗ 0 Cardinality means empty table

→ Keys in RDBMS

The Integrity of the info stored in a DBMS  
is controlled by keys .

- A Key is a attribute or a set of attributes which are used to uniquely identify every row or a record in a table.
- A Key is normally correlated with one column in a table, although it might be associated with multiple columns.
- A Key is used to sort the data i.e. arranging the records either in ascending order or descending order.
- Keys are also referred as sort Keys, index Key or Keywords.

### Types of Keys →

- combination of columns that uniquely identifies any row within a RDBMS
- 1) Super Key - A super Key is a set of one or more attributes that collectively allow us to uniquely identify a tuple in a relation. It supports NULL value.

id	Name	Marks	Dept	Course	
1	a	10	CS	C1	$K_1 = \{id\}$
2	b	7	EE	C2	$K_2 = \{id, name\}$
3	a	8	CS	C3	$K_3 = \{id, name, dept\}$
4	b	7	EE	C2	$K_4 = \{id, name, dept, course\}$

Sort Key / Index Key / Keyword =

$SK_1 = \{id\}$

$SK_2 = \{id, name\}$

$SK_3 = \{id, name, dept\}$

$SK_4 = \{id, name, dept, course\}$

sup

## 2) Candidate Key

The minimal SuperKey is called as Candidate Key. Each candidate Key must satisfy following 2 properties

i) Uniqueness

ii) Irreducible  $\rightarrow$  cannot be decomposed or reduced

for ex -  $XY$  is a Super Key and  $X$  is also a SuperKey then  $XY$  can never be a Candidate Key.

$XY \rightarrow S.K$

$X \rightarrow SK$

$XY \rightarrow X.C.K$

## 3) Primary Key - it denotes a Key i.e. chosen by database designer as the principal means of identifying unique records within a relation.

The primary Key should be chosen in such a way that its value must not change.

Ex - enrollment id can be designated as primary Key.

## 4) Composite Key.

It is a key composed of more than one column or attribute. It is also known as concatenated Key or Structured Key.

All Keys other than primary Key are Composite Keys.

5) Foreign Key: It is a column in a table (parent table) that references a primary key in another table (child table)

6) Alternate Key: It is the key that has not been selected to be primary key but are candidate key. or

Any candidate key other than the one chosen as a primary key is called alternate key.

for ex- id, name, address are candidate keys. Select (id) as primary key & rest of candidate key (name, address) are alternate keys.

7) Secondary Keys

It is key used to speedup the searches and retrieval. It does not necessarily contains unique values

of Relational Schema

$R(A_1, A_2, A_3, A_4, \dots, A_n)$

is made up of relation name (R) and the list of attributes

## Relation

Emp (id, name, address)

→ defined as a set of tuples, let R be a relation which contains set of tuples  $(t_1, t_2, \dots, t_n)$ . Each tuple is an ordered list of n values i.e.  
 $t = (v_1, v_2, v_3, \dots, v_n)$

## Integrity Constraints

- These are set of rules
- Used to maintain the quality of information.

Integrity constraint ensure that the data insertion, updating and other processes have to be performed in such a way that data integrity is not affected.

Thus, integrity constraint is used to guard against accidental damage to the database.

→ Types of Integrity constraints:

Domain constraint can be defined as the definition of valid set of values for an attribute.

The datatype of domain includes string, character, integer, time, date, etc.

Name	id	Age
abc	1	18
xuz	2	A → Not allowed.

PK is used, it can't be NULL

## 2. Entity Integrity Constraint

The entity integrity constraint states that Primary Key value can't be NULL

This is because PK value is used to identify individual rows in relation. and if the primary key has a NULL value, then we can't identify those rows.

And if the primary key has a null value we cannot identify those rows.

A table can contain a null value other than the primary key field

Name	id	age
abc	1	18
xyz	↓	12
	NULL	NOT
		allowed

## Referential Integrity Constraints

ename	eid	age	did
Shivani	1	17	11
Ab	2	18	12
C	3	19	14 ←
			NA

did	dname
11	a
12	b
13	c

A referential integrity constraint is specified b/w 2 tables.

In referential integrity constraint, if a foreign key in table 1 refers to the primary

Key in table 2, then every value of foreign key in table 1 must be available in table 2.

#### 4) Key Constraints

ename	eid
A	01
B	02
C	02 → Not allowed

i) Key are the entity set that is used to identify an entity within its relation uniquely.

Key constraints states that a primary key must contain a unique value, it cannot have duplicate values.

## SQL Commands

DDL	DML	DCL	TCL	DDL
Create	Insert	Grant	Commit	Select
Drop	Update	Revoke	Rollback	
Alter	Delete			
Truncate				

DDL - It change the structure of the table like creating, altering a table.

All changes are auto committed that is permanently saves all the change in database.

- Drop - used to delete both structure & records stored in the table

Drop table tablename;

alter - used to alter structure ~~and~~ of the table / database. Change could be either to modify characteristics of existing attributes or to hide an attribute.

Alter table tablename

Add colname definition; or  
modify oldname newname;

Truncate - it is used to delete all rows from the table and free the space containing that table.

truncate table tablename;

## 2) DML - Data Manipulation Language

used to modify the database. It is responsible for all the forms of changes in a database.

Commands are not auto-committed. They can be rolled back.

Delete → It remove all rows one at a time and holds an entry in

transaction log for each deleted row.

Delete from emp where id = 1;

3) DCL - used to grant and take back authority from any database user.

Grant - used to give user access privately a database.

Revoke - used to take back permission from user.

4) TCL - Transaction Control language. Can only be used with DML commands like insert delete update.

Commit; It is used to save all the transactions to the database.

Rollback: used to undo the transactions that to a certain point ~~without rolling back entire transaction~~. that have not already being save through the database.

Savepoint - use to roll the transactions that to a certain point without rolling back entire transaction.

Savepoint savepointname;  
Roll back to savepoint;