



HANDWRITTEN NOTES

Download FREE Notes for Computer Science and related resources only at

[Kwiknotes.in](https://kwiknotes.in)

Don't forget to check out our social media handles, do share with your friends.



Tooltip, Popover, Do plugins from Yahoo Base
vd = 45.

BOOTSTRAP

Popular among frameworks, for mobile friendly sites, free, opensource

Made with Sass variables
Uses grid system

Allow to use JS comps. like slider

Setup

- 1) Through CDN (Content Delivery N/w)
1 CSS link & 4 js script
- 2) Installation

```
<meta name="viewport" content="width=device-width, initial-scale=1" >
```

To use with React

on google type npm on first link
click search bootstrap

2 In react project npm install bootstrap

btn btn-success - green button

```
Admin App.js  
import "!!/node_modules/bootstrap/dist/css  
/bootstrap.min.css";
```

Start using utility class in className

Container <div class="container">
Makes text centered.

1) Borders to change border style & radius, remove all border or some

border - 0	no border	
border - top - 0	remove top border	
border - bottom - 0	bottom	
border - left - 0	Left	
border - right - 0	Right	
rounded	add rounded border	
rounded - top		
rounded - left		
rounded - right		
rounded - bottom		
rounded - circle		100%
rounded - 0		

2) Clearfix - when we assign parent element to float left, child will also float to left. So, clearfix is used to clear floats by adding .clearfix to parent element.

className = "clearfix" ⇒ to remove floating properties of prev elements.

3) Default Colors By Bootstrap Utility Class.

text-muted - light gray
text-primary - light blue
text-success - light green
text-info - more light blue
text-warning - yellow
text-danger - red

bg-muted - gray bg [all]

or in case of button
btn-primary

"btn btn-primary" - blue button with btn properties with hover

Display - how element is arranged in DOM

d-block block display 
d-inline inline display 

d-inline-block pehle inline fill krega when line ends moves to next line.

Bootstrap Utilities - Image Replacement

```
<h3 className = "text-hide" style =  
"background-image: url('user.png');" > Heading 3  
</h3 >
```

Buttons

```
<button className = "btn btn-primary"  
type = 'Submit' value = "Sub Button" > /button >  
⇒ Blue button will show up
```

```
<button type = "button" className =  
"btn btn-outline-primary" > Primary </button >
```


Primary

No color fill only
blue outline button

btn-lg large
 button


btn-sm small
 button

btn-group-lg



large

btn-group



normal

btn-group-sm




small

```
<button type="button" className="btn btn-lg btn-info disabled"> Button
</button>
```

```
<div className="d-grid gap-2">
  <button class="btn-info"> B1 </button>
  <button className="btn-info"> B2 </button>
</div>
```

<div>



d-flex



d-md-block

mx-auto - center horizontal

justify-content-md-end -> end me align

Grouping Buttons

```
<div class="btn-group" role="group"
  aria-label="Basic ex">
  <button> 1
  <button> 2
</div>
```

Checkbox Button

```
<input type="button" className="btn-check"
  checked=""> Check Button
```

Invisible Content

Set visibility to hidden, & it takes up required space.

className = 'Invisible'

display: none don't acquire space

Positioning

fixed - top
fixed - bottom

fix content to top
fix content to left bottom

Sticky - top
touch hoga krne pr upar
Element jha b h jb vo upar
to fix hogaga or scroll
apni jagah pr vapis aajaega

Responsiveness

important! is included to avoid specificity issues.

These use same viewport width breakpoints as grid system.

float - left , float - right , float - none

sm → for small size devices like phone

md - 768 pixel or more like tab

lg - large device like laptop

xl - like led TV.

xs - extra small, phone < 1200px

float-sm-left

float-md-left

float-lg-left

float-xl-left

Screen Reader

for reading devices.

sr-only - only visible in DOM

sr-only-focusable - visible on tab click

Sizing

width ⇒ w - value in percent

height ⇒ h - value in percent

w-25 25% width

max-height: 100
max-height: 100

Limitations

* we can only give 25, 50, 75, 100

* Can't give in pixel, only percent
auto - take parent width

```
<div className='outer' >
```

```
<div className='h-25' > </div >
```


```
</div >
```

.outer {

height: 100px;

}

100px



vh-100 → viewport 100

vw-100 → full width

padding: top Right Bottom Left

Spacing

⇒ to reduce use of media query

Property ⇒ Margin

Side ⇒ top, bottom, left, Right

Size ⇒ value

Breakpoint ⇒ sm, md, lg-xl

m margin padding right Left-
top bottom

x left & right

y top & bottom

blank used for classes that set a margin or padding on all 4 sides of ele
ex - m-40, 40 margin all sides.

⊛ But for this we need to give CSS

.m-1 ↓

margin: 1px; ↓

so m-1 can be used

Spinner

Spinner - border 0 always moving

Spinner - border text-muted - gray

" text-primary blue

text-info - light blue

text-dark

text-light, danger, warning

text - success - green  green

Spinner - grow 

Spinner - grow text - danger  → Red growing

Tooltip - used for desc when we hover on icon & < a>

SYNTAX

data - toggle = "tooltip" title = "I am tooltip"

We need to explicitly define tooltip in js scrip

```
$document.ready(function () {
```

```
  $('[data-toggle = "tool-tip"]').tooltip(),
```

```
});
```

⇒ not working see yt.

Date Time Picker

```
<input type = 'date' name = "date" >
```

html

m/m/ d/d/ y/yy

Yahoo Baba

Container


```
classname = 'container'
```

Text

1140px

Container-fluid

100% area



Container

incli margin

15px height automatically

.row should be used

within .container only.

.col ⇒ to divide vertically in equal with

```
<div className = 'col' >
```

```
<div className = 'row' >
```

```
<div className = 'col' > 1 </div >
```

```
<div className = 'col' > 2 </div >
```

```
</div > <div className = 'row' > hello </div >
```

```
</div >
```

jese hi overflow hoga
 flex direction apne aap
 column hogayi & width will change acc.

@ `<div className = "w-100"> </div>`
 ↳ similar to `
`


If i want particular column in each row
 ex-)

`<div className = 'row row-cols-2'> --- </div>`

Extralarge	col-xl	xl
Large	col-lg	lg
Small	col-sm	sm
medium	col-md	md

Grid System

Acc to Bootstrap Grid Sy



• col-6



• col-8



<div className = 'row'>

<div className = 'col-8'> 8 block </div>


<div className = 'col-3'> 3 block </div>

<div className = 'col-5'> 5 block </div>

</div>




5 block in next line because $8+3+5 > 12$
& 12 grids hi limit h.



~~★ imp~~

col - md - 8

medium large & xl tk 8 bits use chota
note apne aap flex direction column



Offset - subset for col class to give grid block space or not to start from beginning



offset-md-3 → after 3 screens.

```
<div className = "col-md-5 offset-lg-1  
offset-md-3" > - - - </div>
```

- col-md-5 → medium screen tk 5 grids ka hoga after that flex column hojega
- offset-lg-1 → large screen m 1 block ka space
- offset-md-3 → medium part hi 3 ka space after that flex column hojega


Reordering col class

order-first → on first post
order-last → on last position

Regardless of wherever they are written

ex-order-md-last, order-lg-first

↳ medium tk last me rhege uske bad apni position p.



Nesting col under col class

```

<div className = "container">
  <div className = "row">
    <div className = "col-md-6">
      <h2> heading </h2>
      <div className = "row">
        <div className = "col-md-6">
          <h3> Sub head </h3>
        </div>
        <div className = "col-md-6">
          <h3> col2 </h3>
        </div>
      </div>
    </div>
  </div>
</div>

```

Margins

m-auto margin auto (m-xl-auto)
 ml-auto margin left auto mtlb right:0
 mr-auto margin Right auto
 m-lg-auto large screen tk auto
 uske baad auto margin don't work

Margin	m	
Margin-Right	mr	D-S sizes available
-Left	ml	
-Top	mt	
-Bottom	mb	

0	0px	→ Same for all
1	0.25 rem	
2	0.50 rem	
3	1 rem	
4	1.5 rem	
5	3 rem	

6" → `mr - lg - 5` - largescreen +K 5 margin from right else 0.

-6' → `mr - lg - n5` → - more towards left negative may overlap.

:/div

Padding

to) `p` padding `pl` left `pr` Right
`pt` Top `pb` Bottom


`p-5` ⇒ 3rem all sides

`pl-2` ⇒ 0.50rem from left


`pl-md-2` ⇒ medium +K 0.5 rem padding. case niched

Horizontal Align


justify-content-end



justify-content-center




justify-content-around




justify-content-md-end => medium + end
me use baad normal left one.

Vertical Align

Align-item-start




align-item-end



Chote islieh
kyki centered
kam h.

align-item-center



`align-item-stretch`
↳ default view.





`align-item-xl-start`, `align-item-md-end`,
we can use them with `md`, `lg`, `xl`

Similarly `Align Content` is used
Ex- `align-content-md-around`
to align data inside row - same property of
`align-item`

Particular alignment - just for one div

`align-self-start`, `end`, `center`, `stretch`, `auto`

```
<div className="row align-item-start">  
  <div className="col-md-3  
    align-self-center">  
    <div> </div> </div> </div>
```



Flex Direction

A B C D - flex-row-reverse - D C B A

A]
B] flex-column
C]
D]

D]
C] flex-column-
B] reverse
A]

Display


d-flex, inline-block

<div className="d-lg-inline-block">

large tk



baadm



display - d

d-none, d-flex, d-inline-block,
d-block

d-md-none, d-xl-flex

If I have two divs on one I applied
<div className="d-none d-sm-block">
<sm tk block m, ts me gayab.

Overflow overflow-auto, overflow-hidden

Text Align

text-left, text-right, text-center, text-justify

text-xl-left, text-md-center

Text Transform

text-lower, text-uppercase, text-capitalize

font height

font-weight-bold, font-weight-bolder

font-weight-light, font-weight-lighter

font-weight-normal

font-italic, text-monospace (font)

Anchor text-decoration-none

• text-reset ⇒ makes color of anchor tag same as parent div.

text-wrap →

text-truncate extra text to ...

text-break moves text to next line of div

List Style

list-unstyled → remove bullets

list-inline → all in one line

on list-inline-item

display-1, display-2, display-3, display-4

Headings

lead → para fonts.

give slim fonts

Block Quote

<blockquote>

<p> - - - </p>

<footer className="blockquote-footer">
Name </footer>

</blockquote>

User Select

- user-select-auto ⇒ normal select
user-select-all ⇒ one click p pura
 div select
user-select-none ⇒ can't select

List Group

list-group



list1
list2
list3


↑ flush

```
<ul className="list-group" >  
  <li className="list-group-item" > 1 </li>  
  <li className="list-group-item" > 2 </li>  
</ul>
```

↓



1
2



```
<ul className="list-group list-group-flush" >  
  <li className="list-group-item" > 1 </li>  
  <li > -- 2 </li>  
</ul>
```

list-group-item active ⇒ Blue bg

list-group-item disabled ⇒ Grey font
Select nhi hogi

list-group-item-primary ⇒ Blue

- success ⇒ green

- danger

- warning

- info

- dark

all used with
list-group-item

Both classes to add


list-group-item-info

Horizontal Lists

l1 | l2 | l3 | l4

we can also give break points like md, lg-sm
after that they will become vertical

```
<ul className="list-group list-group-horizontal">  
> <li className="list-group-item"> | </li>
```

list-group-horizontal-md
⇒ After md, they will become vertical

⇒ work properly in div

In li use .list-group-item-action

⇒ this makes whole list row highlight when we hover just like menu

```
<div className = "list-group">  
<a href = "#" className = "list-group-item  
list-group-item-action"> 1 </a>  
<a href = "" className = "list-group-item  
list-group-item-action"> 1 </a>
```

Now when we will hover, it will highlight.

⇒ ~~Binary~~ ⇒ (can also give colors
like primary, info by adding

list-group-item - primary

Table Classes

className = "table"

Others

table-dark, table-Striped
table-borderless, table-bordered
thead-dark, thead-light

Pagination

→ mainly used inside `<nav>` tag, makes tags inline `<nav>`

```
<ul class='pagination'>  
  <li className='page-item'>  
    <a href='#' className='page-link'>  
      </a> </li>  
</ul> </nav>
```

Active `<li className='page-item active'>`
` | `

Disabled 'pag-item disabled'
Large pagination - lg
Small pagination - sm

Breadcrumb Class

Home/Lib/Class

```
<nav> <ol className='breadcrumb'>  
  <li className='breadcrumb-item'>  
    <a href='#'> Home </a> </li>  
</ol>  
</nav>
```

Active 'breadcrumb-item active'

Bootstrap 5 Alpha Version

Introduced for testing purpose

Easy Documentation

Jquery Removed

Still has Jquery plugins, filesize Reduced

New breakpoints ⇒ Extra Extra large
(XXL) introduced ≥ 1320 px

Forms .form-group

```
<div className = 'form-group'>  
  <label> Name </label>  
  <input type = 'text' className = 'form-control'>  
</div>
```

Descriptive text

```
<input type = 'Password' className = 'form-control'>  
<small className = 'form-text text-muted'>  
  Password must be 8 character  
</small>
```

Readonly field

```
<input type='text' value='abc'  
className='form-control-plaintext' readonly/>
```

Large text

• form-control-lg

Small text

• form-control-sm

File

form-control-file

Range

form-control-range

Checkbox

• form-check → Div

• form-check-label → Option

```
<div className='form-check' >
```

```
<input type='checkbox' className='form-check-  
-input' id='val1' />
```

```
<label for='val1' className='form-check-  
label' > Value1 </label >
```


Radio

```
<div className='form-check' >
```

```
<input type='radio' className='form-check-  
input' name='gender' id='male' />
```

```
<label for='male' className='form-check-  
label' > Male </label >
```

Inline form `.form-inline`



each input field under div of form group

```
<form action="" className="form-inline">
  <div className="form-group">
    <input type="text" class="form-control"
      placeholder="User Name" />
  </div>
</form>
```

`form-row` \Rightarrow Row with form fields.

Responsive form using col

```
<form className="row py-3" or form-row>
  <div className="col-md-4">
    <input type="text" className="form-control"
      placeholder="Name" />
  </div>
</form>
```

No need of form group / inline. Maintain Margin

Inline Checkbox `form-check-inline`

Value
`form-check-label`
`form-check-input`

```
<div className='row'><div className='col py-3'>
```

```
1 <div className='form-check form-check-inline'>  
  <input class='form-check-input'>  
  <label -->  
</div>
```

Same for Radio

Horizontal form

Name

Gender M F

```
<div className='row'>
```

```
<div className='col'>
```

```
  <form>
```

```
    <div className='form-group row'>
```

```
      <label className='col-form-label'> Name </label>
```

```
      <div className='col-sm-1'>
```

```
        <input type='text' />
```


This whole for one ~~input~~ input

```
<input type='text' className='form-control'
>
</div>
</div>
```

Form Custom Class

1)

```
<select name='' className='custom-select'
  <option value='1'>1 </option
</select>
```



2)

```
<input type='file' class='custom-file-input'
label className='custom-file-label'>choose </label>
```

(Choose Browse)

3) custom-range for Range

4) custom-control-input val1
custom-control-label val2
main div me ⇒ custom-control custom-checkbox

5) custom-control custom-switch

```
<input type='checkbox' class='custom-
control-input'>
<label> - - -
```

\$

```
<div className='input-group'>  
  <div className='input-group-prepend'>  
    <span className='input-group-text'>  
      $ </span>  
  </div>  
  <input type='text' className='form-control'>  
</div>
```

example@.net

```
<div className='input-group'>  
  <input class='form-control' type='text' />  
  <div className='input-group-append'>  
    <span className='input-group-text'>  
      @example.net </span>  
  </div>  
</div>
```


\$ 1.00

```
<div className='input-group'>  
  <div className='input-group-prepend'>  
    <span className='input-group-text'> $  
  </span> </div>  
  <input class='form-control' type='text' />  
  <div className='input-group-append'>  
    <span className='input-group-text'>  
      .00 </span>  
  </div>  
</div>
```

We can directly use `<a>` under ~~the~~
`<nav class='nav'>`
` `

Navs

```
<ul className='nav'>  
  <li className='nav-item'> |  
    <a href=' ' className='nav-link'>  
      home </a>  
  </li>  
</ul>
```

nav-pills \Rightarrow 

nav-fill \Rightarrow cover full row

navbar-brand \Rightarrow for logo

Navbar

```
<div className='row'>  
  <div className='col'>  
    <nav className='navbar navbar-expand  
-lg navbar-light bg-light'>  
      <a href=' ' className='navbar-brand'>  
        Company Name  
      </a>
```

```

<ul className='navbar-nav'>
  <li className='nav-item'>
    <a className='nav-link' href='1'>
      Home </a> </li>
  <li className='nav-item dropdown'>
    <a href='' className='nav-link
      dropdown-toggle' data-toggle=
        'dropdown'>
      About us </a>
    <div className='dropdown-menu'>
      <a href='' className='dropdown
        -item'> 1 </a>
      <a href='' className='dropdown
        -item'> 2 </a>
    </div>
  </li>
</ul> </div>

```

Hamburger

make a div with class

collapse navbar-collapse & id = mynav

Div must contain navbar with <nav> or

```

<button className='navbar-toggler' data-toggle=
  'collapse' data-target='#mynav'>
  <span className='navbar-toggler-icon'></span>
</button>

```



It will show under the screen
we give with navbar - expand - (lg/sm/md)

Images

.img-fluid	Responsive image
.img-thumbnail	Gives a sleek border with 2px margin padding
rounded	Increase border-radius
rounded-circle	○ almost 50% radius
rounded-top	∩ on top
rounded-bottom	∪ on bottom
rounded-left	[
rounded-right]
rounded-pill	Border Radius from Right like capsule

Figure with Caption

```
<div className = 'col-md-4'>  
  <figure className = 'figure'>  
    <img src = ' ' className = 'figure-img  
    img-fluid' >  
    <figcaption className = 'figure-caption'  
    Caption here  
  </figcaption >  
</figure >  
</div >
```

1/nd

```
<div className = 'embed - Responsive' >  
  • embed-responsive - 21 by 9  
  • embed-responsive - 16 by 9  
  • embed-responsive - 4 by 3  
  • embed-responsive - 1 by 1  
</frame = class = 'embed-responsive-item'  
  src = ' ' >
```

ng

Border

• border → gives thin gray border
• border-left, • border-right,
border-top, border-bottom

gnt

No Border

border-0, border-top-0, border-right-0
border-bottom-0, border-left-0

Border color Classes

border-primary, border-secondary,
border-danger, border-warning,
border-white, etc.

↳

Shadow

shadow-sm

shadow-lg


shadow

thin

thick

Shadow-none

↳ for no shadow



Card

```

<div className = 'card' >
  <img src = '' className = 'card-img-top'
    alt = '' >
  <div className = 'card-body' >
    <h4 className = 'card-title' > text </h4>
    <p className = 'card-text' > lorem </p>
    <button className = 'btn' > show </button>
  </div>
</div>

```

card-img-bottom ⇒ Text upar image niche

card-img-overlay ⇒ makes image as bg and text on image

```

<h3 className = 'card-subtitle
  text-muted' > </h3>

```

↳ Makes gray text

class - header ⇒ header

class - footer ⇒ footer

* no-gutters

Img | text

card then row then col-md-4 with
img & col-md-8 with text.

g - top

Card Group card-group
<div> with class cards

which contain




</h4>

</p>

</button>

Card Deck card-deck
gives equal padding



* Card-Columns




Masonry layout
like Pinterest.

niche

as

Media Object Class
used for comment



```
<div className='media'>
  <img src='...' className='align-self-center'>
  <div className='media-body'>
    <h1> --- </h1> <p> --- </p>
  </div>
</div>
```

For showing Reply pass full code after
<p> tag, it will be shown as a child

Can be used under ul, li also

Badges

[Notification ④]

Example [New] ^{Blue}

```
<h1> Example <span className='badge badge-primary'> New </span> </h1>
```

```
<h2> Example <span className='badge badge-pill badge-success'> New </span> </h2>
```


Example (New) ^{Green, pill shape.}

```
<button className='btn btn-primary'> Notification <span className='badge badge-light'> 5 </span> </button>
```


[Notification ⑤]

```
<a href='...' className='badge badge-info'> Read </a>
```

Progress Bar



Jumbotron



• jumbotron-fluid \Rightarrow full width

```
<div className = 'jumbotron' >
  <h1 > - - </h1>
  <p > - - </p> <hr / >
  <p > - - </p>
  <button > See more </button >
```

By default bg-color is gray & border rounded

With image as bg

Give id to div & in css file

idname {

background: url(' ') no-repeat;

background-size: cover;

Alerts

```
<div className = 'alert alert - primary' >
  text - - - <button className = 'close' >
  <span > & times; </span >
</div >
```

```
<div className = 'alert alert - primary' >
  text <button className = 'close' data-dismiss =
  'alert' > <span > & times; </span >
</button >
</div >
```